



Podnośniki dwu nożycowe poziome

Sprzedaż – Serwis
HYDROMECHANIKA M.R.
www.HYDROMECHANIKA.pl

Art.nr	Model	Udźwig (kg)	Wymiary platformy (mm)	Skok (mm)	W sta. złożonym (mm)	Czas podnosz. (s)	Silnik (kW)	Waga (kg)
40206	TLXX-10/82-2C	1000	2700x800	820	230	23	0,8	320
40207	TLXX-10/110-2C	1000	3400x900	1100	230	38	0,8	580
40208	TLXX-10/160-4C	1000	4400x1200	1600	300	37	2,3	800
40201	TLXX-20/82-2C	2000	2700x800	820	230	42	0,8	330
40211	TLXX-20/110-2C	2000	3400x900	1100	230	68	0,8	600
40221	TLXX-20/160-4C	2000	4400x1200	1600	300	37	2,3	900
40202	TLXX-30/82-4C	3000	2700x800	820	260	28	2,3	390
40212	TLXX-30/110-4C	3000	3400x900	1100	260	45	2,3	620
40222	TLXX-30/160-4C	3000	4400x1200	1600	300	66	2,3	920
40203	TLXX-40/82-4C	4000	2700x800	820	260	28	2,3	390
40213	TLXX-40/110-4C	4000	3400x900	1100	260	45	2,3	620
40223	TLXX-40/160-4C	4000	4400x1200	1600	300	66	2,3	950
40204	TLXX-60/82-4C	6000	2700x800	820	260	27	3,5	490
40214	TLXX-60/110-6C	6000	3400x900	1100	300	50	3,5	680
40224	TLXX-60/160-4C	6000	4400x1200	1600	300	62	3,5	1090
40225	TLXX-60/160-4C	6000	5000x1500	1600	300	62	3,5	1420
40226	TLXX-60/160-4C	6000	6000x2000	1600	300	62	3,5	1560
40205	TLXX-80/82-6C	8000	2700x800	820	300	40	3,5	560
40215	TLXX-80/110-6C	8000	3400x900	1100	300	65	3,5	770
40227	TLXX-80/160-6C	8000	4400x1200	1600	350	62	5,5	1600
40228	TLXX-80/160-6C	8000	5000x1500	1600	350	62	5,5	1750
40229	TLXX-80/160-6C	8000	6000x2000	1600	350	62	5,5	1860

